

HONEYWELL FUEL OIL METERS

Industrial Fuel Oil Meters · Sizes 1/8" and 1/4"

Building managers have more tools to control their facility's systems. They need accurate reliable meters to provide input data.

Honeywell oil meters provide fuel consumption measurements to users in flexible formats. Whether directly displaying totalization, showing consumption in an accessible location, or providing high resolution information to user's systems, the oil meters fulfill user's needs for accurate, reliable information.

OPERATION

This Honeywell line of compact high precision oscillating piston oil meters covers a range of flows from 0.25 to 50 GPH. These meters are capable of measuring light heating oil, diesel, and even gasoline. Accuracy is $\pm 1\%$ throughout the operating flow range for each meter. Each meter is tested with #2 fuel oil at 70°F to verify the accuracy.

Typical applications of these Honeywell oil meters include: Measuring heating oil consumption in burners for heating units and industrial furnaces; measuring fuel consumption in land-based and sea-based diesel and gasoline engines including emergency power generators; industrial batching applications.

The meters should be sized according to anticipated flow rates for the system. Users may install piping reducers to fit a properly sized meter into existing piping. The user has the option of mounting these meters horizontally, vertically, or on any plane in between. Honeywell oil meters include a register face that features a 1:1 piston ratio low-flow indicator to detect plumbing leaks and a high resolution sweep hand on the register.

Pulse unit versions of the Honeywell 4 (1/8") and Honeywell 8 (1/4") are available to allow interfacing for batch operations, rate of flow indication, or remote readouts and control. Registration is retained even with the addition of a pulse output to either the Honeywell 4 or Honeywell 8. Compatible electronic equipment is available from Honeywell.



Honeywell 4 and Honeywell 8 industrial oil meters are capable of measuring light heating oil, diesel, and even gasoline.

FEATURES AND BENEFITS

POSITIVE DISPLACEMENT MEASURING PRINCIPLE

Immune to turbulent flow effects.

RUGGED OSCILLATING PISTON DESIGN

Measures a wide range of fluid viscosities.

OPTIONAL PULSE OUTPUT

Simple integration into building management systems.

Honeywell

MATERIALS

Meter Body: Brass

Cover: Oil proof polymer

Working Chamber: Brass

Shutter: Brass

O-Rings: Buna N (Honeywell 4),

Viton (Honeywell 8)

Piston: Anodized aluminum

Safety Filter: 316 stainless steel

REED SWITCH PULSER

- 2-wire system
- Max voltage: 48 VAC/VDC
- Max current: 50 mA
- Max switch power: 3W
- Max resistor (47 Ohm) power: 0.5W
- On time: 50 ± 20%
- No cable supplied

Note: This pulser is not polarity (+/-) sensitive.

	HONEYWELL 4	HONEYWELL 8
PERFORMANCE	1/8"	1/4"
Minimum Flow GPH (l/h)	0.25 (1)	1 (4)
Max Rec Cont Flow GPH (l/h) ¹	14 (50)	35 (135)
Peak Flow GPH (l/h)	20 (80)	50 (200)
Accuracy	±1%	±1%
Max Operating Pressure psi (bar)	355 (25)	355 (25)
Max Operating Temp °F (°C)	140 (60)	140 (60)

REGISTER READING	1/8"	1/4"
Smallest Quantity USG (l)	0.001 (0.001)	0.01 (0.01)
Capacity in Millions USG (l)	0.1 (0.1)	0.1 (0.1)

PHYSICAL DESCRIPTION	1/8"	1/4"
Threaded Connection Type ²	1/8" FNPT	1/4" FNPT
Safety Filter Mesh (included)	120	100
Recommended Strainer Mesh	200	140


OPTIONAL PULSE UNITS	1/8"	1/4"
Reed Pulser - Pulses/USG (pulses/l)	10 (10, 100, or 800)	1216 (1 or 321.5)

1. Meter selection should be based on the maximum recommended continuous flow rating.
2. Using the provided adapters.


DIMENSIONS AND NET WEIGHT

METER SIZE	A	B	C	D	E	Weight
	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)	lbs. (kg)
1/8"	2.50 (65)	3.125 (79)	2.50 (65)	0.725 (18)	0.875 (23)	1.5 (0.7)
1/4"	2.50 (65)	3.125 (79)	2.50 (65)	0.725 (18)	0.875 (23)	1.8 (0.8)


Note: All dimensions are ±1/16".



Side



Front



Bottom

Find Out More

WaterMeters@honeywell.com

www.elsteramcowater.com

Honeywell Smart Energy

10 SW 49th Avenue, Bldg. 100

Ocala, FL 34474

T +1 800 874 0890

F +1 352 368 1950

1100 Walker's Line, Suite 302

Burlington, Ontario L7N 2G3

T 866 703 7582

F 905 634 6705

www.HoneywellSmartEnergy.com

SEW-DS-NAEN-OIL48 | 08/19
© 2019 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell