



# TS10A, 1"

## Anodized Aluminum, Electronic

- Only two moving parts
- No metal to metal contact in chamber or bearings
- Internal pulser = Gland-less meter design
- Patented 'Wave Form' oval gear design
- Low differential pressure for maximum flow

### Specifications

- **Nominal Capacity with standard LV rotors**


To 1500 SSU visc. :	<b>40 GPM</b>	} <i>NTEP</i> 5:1 turn-down <i>Industrial to 30:1 turn-down</i>
To 300 cP viscosity :	<b>150 lpm</b>	
To 300 cP viscosity :	<b>9 m<sup>3</sup>/h</b>	
- **Pressure Rating**
  - Meter & Strainer** : 400 PSI at 100°F = 28 BAR at 40°C
  - Air Elim & Valve** : 150 PSI at 100°F = 10 BAR at 40°C
- **Temperature Rating** *See note under Signal Conditioners*
  - Design, W Assy.** : -40°F to +257°F = -40°C to +125°C
  - ATEX listing** : -4°F to +140°F = -20°C to +60°C
  - Design, F Assy.** : Same, *subject to register temperature limits!*
- **Viscosity**
  - With **LV** rotors : 100% capacity to 1,500 SSU (300 cP).
  - With **HV** rotors : 100% capacity to 5,000 SSU (1000 cP),  
reduced capacity to 1,500,000 SSU (350,000 cP).
- **1" Connections** Bolted companion flanges with NPT or BSP port.  
Optional : Bolted welding flanges, anodized aluminum
- **Materials** **100% Non-Ferrous**
  - Case : Anodized aluminum
  - Gears : PPS with carbon bearings, Teflon™ bearings opt.
  - Posts : HC303SS
  - Seals : Viton™ standard, Teflon™ optional.
  - Flanges : Anodized aluminum std., carbon steel optional.
- **Pulser** : **Hall Effect Quadrature**,  
5V reg or 6-12V non-reg; pls consult for 24V DC.
- **K Factor** : Nominal 1728 PPG (456.5 ppl) on 1 cP viscosity,  
Opt. with SCL : EL0300-3-13B = 100 PPG (26.5 ppl)  
EL0300-3-18B = 10 PPL (37.85 PPG)

### TS10AW04AATU for remote electronic register

Depending upon register or controller model, the pulser compartment in flow sensor front cover holds the sensor (pulser), and either:

- A. **TBB** = Terminal Block Board
- B. **SCL** = Scaler/Calibrator/Linearizer

### Meter Performance

- Linearity** Over 5:1 turn-down from max. capacity: ±0.175%  
Over 10:1 turn-down from max. capacity: ±0.25%  
Over 30:1 turn-down from max. capacity: ±0.5%
- Repeatability** 0.05% or better under constant conditions
- Approvals** Custody Transfer approvals are liquid specific.  
W&M approval in the US.
- **Flow Meter** CE mark.
- **Pulser & SCL** *Intrinsically Safe*, UL & cUL listed,  
**SCL also EEx ia ATEX**  
when powered through *approved barrier*.
- **Pulser encl.**  II 2G Ex d IIA T4, -20°C <T<sub>a</sub><+60°C,  
ATEX, IEC Ex & IP65

### Registration, Signals & Accessories

- **Electronic registers:**  
Tuthill electronic flow meters will support most common electronic registers & controllers. Available through Tuthill:
    - **ELNC** W&M register for stationary service
    - **EMR<sup>3</sup>** W&M register for stationary or truck service
    - **PC58** Totalizer/Rate meter (non-W&M)
  - **Signal Conditioners:**
    - **EL0300** SCL Scaler, Calibrator and/or Linearizer.
    - **EL6630** PIA-300 amplifier for remote register (to 2,500' = 750 m)
    - **PC58** with optional 4-20 mA signal or multi-point calibration.
- NOTE:** *If EL0300 is used in place of EL0304, max liquid temperature = 185°F (85°C). For higher liquid temperatures, these components must be mounted remote from the flow meter in a separate enclosure.*
- **Accessories** If strainer, air eliminator and/or preset valve are required, please see model TS15A.  
1/10 liter register, 10 PPL, 100 PPL

**Tuthill Transfer Systems** Phone: 800-634-2695  
8825 Aviation Drive, Fax: 800-866-4861  
Fort Wayne, IN 46809 USA E-mail: fillrite@tuthill.com



ISO 9001:2000 Certified

International offices:	Phone	Fax
Europe, Middle East & Africa - Belgium Office	+32 (10) 22 83 34	+32 (10) 22 83 38
Europe, Middle East & Africa - UK Office	+44 (115) 932-5226	+44 (115) 932-2526
Mexico (North)	+52 (81) 8303-0025	+52 (81) 8303-6334
Mexico (South)/Caribbean/Centr. America	+52 (55) 5370-2626	+52 (55) 5370-0602
South America	+54 (11) 4116-2830	+54 (11) 4116-2835
Australia/Pacific Rim	+61 (3) 9726-2900	+61 (3) 9725-2663
China	+86 (21) 6917-1999	+86 (21) 6917-2162

