

What's new in 2025?



AQUAMETRO CONTOIL® Fuelmeter



VZO 4 and 8 OEM meter
double amount of pulses
each piston rotation; for higher resolution
VZO 4 OEM-RE0.0025
VZO 8 OEM-RE0.00622
VZO 8E OEM-RE0.00622 higher flowrate



VZFA II
for low flow rate and higher viscosity
(gravimetric feeding of lube oil); PEEK piston
VZFA II 15P RC 130/16
VZFA II 15P FL 130/25



VZD2 4 and 8
2nd version of VZD with Modbus
and programmable pulse output
VZD2-4S
VZD2-8S
VZD2-8ES higher flowrate



VZFA II 15...50 with flanges
Oil meter for aggressive and
biological fuels
VZFA II 15..50B FL 180/40



VZF II 15/VZO 15 threaded ends
extended flowrate (40 - 1000l/h)
VZF II 15E RC 130/16
VZO 15E RC 130/16
VZO 15E RC 130/16-RV1
VZO 15E RC 130/16-IN0,01



VZD2 - 4 and 8 stainless steel/PEEK
2nd version of VZD with Modbus
and programmable pulse output
Stainless steel body and PEEK piston
for biofuels and aggressive liquids

Oil meter with wafer flange
VZF II 20...25 AW 130/16
VZO 20...25 AW 130/16

